









Prisma is an easy-to-maintain, absorbent, walk-off entrance carpet in seven warm colours, for homes and small offices.

Design

Prisma is a low-pile, glossy, walk-off entrance carpet with a cut, friséed pile for a subtle shadow effect. The lustre of the yarn enables bright, fresh uni colours. The sparkling scarlet colourway, for instance, means entrance areas can provide a real red-carpet welcome. The golden beige and copper browns complement the metals used in interior furniture fittings and lamps, as do the steel grey and the deep black tones. The midnight blue colour is a surprising combination of grey and black tones, such as those used to powder coat metal window frames and doors.

Matching all floors

Our designers develop colourways that complement every interior style. For ambiences ranging from classic to modern design. The broad Rinos range always has the right solution, to complement both interior design and floor type. **Make your own combination on our website and be inspired by our options.**



Colours



Beige 901 NCS: 8010G90Y



904 NCS: 7020R



902 NCS: 8010Y50R



Grey 908 NCS: 8502G



Indigo 905 NCS: 8505R80B



Red 909 NCS: 3560R



900 NCS: 9000N

Specifications PVC



•		
Pile material	100% Polyamide	100% Polyamide
Pile weight ISO 8543	± 620 gram/m²	± 620 gram/m²
Use classification EN 1307	31	31
Flammability Euroclass EN 13501	Ffl / Cfl/s1	Cfl/s1
Sizes rolls ***	135/200 cm, ± 20 m ¹	135/200 cm, ± 20 m ¹
Sizes mats***	40/60, 60/90, 90/150 cm	40/60, 60/90, 90/150 cm
Backing	Mats: Washable rubber vinyl backing, Rolls: PVC	PU
Absorption capacity TNO W6034	± 5,4 l/m²	± 5,4 l/m²
Total weight ISO 8543	± 2.820 gram/m²	± 2.720 gram/m²
Pile height ISO 1766	± 5,5 mm	± 5,5 mm
Total height ISO 1765	± 7,0 mm	± 7,0 mm
Pile density ISO 8543	0,109 g/cm²	0,109 g/cm²
Number of stitches ISO 1763	± 118.900 /m²	± 118.900 /m²
Wearing class EN 1963	31	31
Comfort EN 1307	LC2	LC2
Dimensional stability ISO 2551	<0,5%	<0,5%
Light fastness ISO 105 B02	5 – 6	5 – 6
Water fastness ISO 105 B01	4 – 5	4 – 5
Rubbing fastness ISO 105 X12	4 – 5	4 – 5
Salt water ISO 105 E02	4 – 5	4 – 5
Shampoo BS 1006	4 – 5	4 – 5
Organic solvents ISO 105 X05	4 – 5	4 – 5
Static charge ISO 6356	< -2,0 kV	<-2,0 kV
Slip Resistance EN 13893	DS	DS
Yarn construction	Frisé	Frisé
Design	Uni	Uni
Colours	7	7
Suitabililty for stairs EN 1963	Occasional use	Occasional use
Suitability for castor chairs EN 985	Occasional use	Occasional use
Primary backing	nonwoven PET/PA	nonwoven PET/PA
Suitability for castor chairs EN 985	NPD	NPD
Primary backing	nonwoven PES/PA	nonwoven PES/PA
Declaration of Performance	Available	Available



^{*} Sand Absorption Class 3: >=90%, Sand Absorption Class 2: 80% =< class 2 < 90%, Sand Absorption Class 1: =< 80% ** Optical Class: 5 is best, 1 is lowest *** All rolls include a PVC edge of 2.5 cm. All mats include a rubber/PVC edge of 1,5 cm. The roll lengths are an indication. Delivered length can be up to 15% higher or lower.



Pura Backing™ is a unique Rinos product innovation, developed by our R&D department. It's the Rinos answer to increasing demand for more environmentally friendly and sustainable entrance mat solutions by avoiding the use of PVC and plasticisers. Mats with Pura Backing™ meet this requirement – with zero PVC and plasticiser content, avoiding stains on porous subfloors. Thanks to increased flexibility, it is even easier to install!

Contact us for more information

Our employees are ready to answer questions or to take your orders. **Call +31 38 385 35 00 or mail customerservice@rinos.com**

Where to use?

	high traffic	medium traffic
Not combined with outdoor matting (scraping)	Α	В
Combined with outdoor matting (absorbing)		D
Outdoor matting	Е	

© Rinos B.V.

rinos.com/products/prisma